

## PLOTTABLE THERMAL ADHESIVE FOR HEAT TRANSFER FOILS

CAD-CUT Adhesive is a plottable heat activated adhesive which is needed for applying heat transfer foils.

Cut the desired design as you would cut a regular flex film, apply adhesive to textile, cover design with heat transfer foil (color side facing up) and press.

That's how easy it is to produce beautiful and shiny foil-embellished designs.



## AVAILABLE IN

30 cm x 9,1 m Rollen

## RECOMMENDED FABRICS

- 100% cotton
- 100% Baumwolle
- Poly/Baumwollgemische
- Polyestergemische
- 100% Polyester

## CUTTING NOTES

You should always test cut prior to any production run. Remember cutter settings will need to be adjusted as the blade ages. For optimal cutting and weeding, maintain a line thickness of at least 2,0 mm for lettering and logos.

## APPLICATION INSTRUCTIONS

- Temperature: 130°C / 150°C
- Time: 10 sec. / 5 sec.
- Pressure: Medium
- (#4-6 on Hotronix®)
- Peel: Hot

## MULTI-COLOUR DESIGNS

## ACCESSORIES RECOMMENDED

- Grip Cover Sheet
- Cover Sheet - Non-Sticky
- EZ Weeder®

## CARE INSTRUCTIONS

Machine wash up to 30° C using mild detergent. Do not use bleach.

Dry at normal dryer settings on household machines.

Do not dry-clean. Can be directly ironed.













## STORAGE

Store in cool, dry area. Avoid direct heat, sunlight and humidity.

## DETAILS



## KEY

 Easy weed	 Thin
 Ironable	 Sticky carrier
 Ironable only inside out	 Multi-colour application
 Washable	 Peel hot
 Sublimation	 Application
 Stretchable	
 Flock	