


CAD-CUT® ADHESIVE



PLOTABLE THERMAL ADHESIVE FOR TRANSFER OF HEAT TRANSFER FOIL

CAD-CUT® Adhesive is a plotable thermal adhesive which is required for transferring the Heat Transfer Foil. simply plot the desired motif as usual, transfer the adhesive to the textile, laminate the motif with the Heat Transfer Foil in the desired color with the foil side facing upwards and print on. this is how quickly you can create beautiful high-gloss designs on the textile.



AVAILABLE IN

30 cm x 9,1 m roll

RECOMMENDED FABRICS * Test before application!

- 100 % Cotton
- 100 % Polyester*
- Cotton-Polyester-blends
- Polyester blended fabric

CUTTING NOTES

Always test the cutting settings before production. Remember that the settings depend on the age of the blade used. To ensure optimum processing of the material, a **minimum line thickness of 1.5 mm is required.**

APPLICATION INSTRUCTIONS

Temperature: 150° C
Time: 10 sec.
Pressure: Light - Medium (#2-6 with Hotronix®)
Carrier: Hot peel

MULTI-COLOR DESIGNS

No overprinting of motifs covered with Heat Transfer Foil possible.

ACCESSORIES RECOMMENDED


- Grip Cover Sheet
- Cover Sheet - Non-Sticky
- EZ Weeder®, LED Weeder, LED Pin or Tweezers

CARE INSTRUCTIONS

Washable up to 30° C. Please do not use fabric softener or bleach. Wash inside out and iron.

STORAGE

Store in a cool, dry environment. Avoid direct heat or sunlight.



CAD-CUT® ADHESIVE



Adhesive