


SWITCHES FROM WHITE TO AN INTENSE COLOR WHEN EXPOSED TO SUNLIGHT.

This PU heat transfer vinyl changes color from simple white to an intense color shade when exposed to sunlight. Indoors, it reverses within a few minutes. CAD-CUT® UV Shift is also ideal for delicate designs, and you can weed it effortlessly.



OEKO TEX* STANDARD TO THE TOTAL TO THE TOTA

AVAILABLE IN

· 50 cmx 25 m rolls

RECOMMENDED FABRICS * Must be tested before proofing!

- 100 % Cotton
- · 100 % Polyester*
- · Cotton-Polyester blends

CUTTING NOTES

Always test the cutting settings before production. The settings depend on the age of the blade used. To ensure optimum processing of the material. Minimum line thickness of 1.5 mm.

CARE INSTRUCTIONS

Washable up to 40° C. Please do not use fabric softener or bleach. Suitable for tumble drying on a gentle setting. Wash and iron inside out.

STORAGE

Store in a cool, dry environment. Avoid direct heat or sunlight.

APPLICATION INSTRUCTIONS

Temperature: 150° C
Time: 10 sec.

Pressure: Medium (#3-4 with Hotronix®)


Carrier: Hot peel

MULTI-COLOR DESIGNS

CAD-CUT® UV Shift is not recommended for multi-layer applications.

ACCESSORIES RECOMMENDED

- · Grip Cover Sheet
- · Cover Sheet Non-Sticky
- EZ Weeder®, LED Weeder, LED Pin or Tweezers





CAD-CUT® UV SHIFT











