

# CAD-COLOR® SUPERTEK™ CLEAR MATT



## HIGH-THICKNESS, TRANSPARENT DIGITAL PRESSURE FILM.

Polyurethane textile printing film, which can also be used to produce large motifs with a soft feel. It has a polyester backing and is equipped with the STiX<sup>2</sup> adhesive, which enables printing on all common types of textile. No need to apply MagicMask, as the material can be printed mirror-inverted and transferred directly to the textile, reducing production time and material costs. Great effects can also be achieved on dark textiles without printing. For brilliantly colored prints, use only on light-colored textiles.



## AVAILABLE IN

- 50 cm x 25 m roll

## RECOMMENDED FABRICS \* Test before application!

- 100% Cotton
- 100% Polyester\*
- Polyester-Cotton blends
- Lycra®- / Spandex blended
- Most nylon textiles\*

## CUTTING NOTES

Always test the cutting settings before production. Remember that the settings depend on the age of the blade used. Cutting too deep will cause difficulties when weeding or pressing.

## APPLICATION INSTRUCTIONS

Temperature: 160° C  
Time: 10 sec.  
Pressure: Medium (#4-8 with Hotronix®)  
Carrier: Warm / Cold peel

## ACCESSORIES RECOMMENDED

- Grip Cover Sheet
- Cover Sheet - Non-Sticky
- EZ Weeder®, LED Weeder, LED Pin or Tweezers

## CARE INSTRUCTIONS

Washable up to 40 degrees. Please check the washability of the fabric. Suitable for tumble drying on a gentle cycle. Not suitable for dry cleaning. Wash and iron inside out. We strongly advise against using liquid detergent, bleach, fabric softener, and laundry pods due to the aggressive ingredients that attack the film.

## STORAGE

Store in a cool, dry environment. Avoid direct heat or sunlight. We recommend not exceeding a storage period of 12 months.

